






166





Pitch: 5.00mm

Approval		
Technical Data	UL	IEC
Rated voltage	300V	450V
Rated current	12A	24A
Conductor cross-section, solid (AWG/mm ²)	18-12	0.5-4
Conductor cross-section, flexible (AWG/mm ²)	18-12	0.5-4
Rated impulse voltage	4KV	
Torque(N-m)	0.34	
Screw	M3	
Wire strip length	6~7mm	



Pole	Cat.No.
02	166-02P
:	:
:	:
30	166-30P




166..P3





Pitch: 7.50mm

Approval		
Technical Data	UL	IEC
Rated voltage	300V	450V
Rated current	12A	24A
Conductor cross-section, solid (AWG/mm ²)	18-12	0.5-4
Conductor cross-section, flexible (AWG/mm ²)	18-12	0.5-4
Rated impulse voltage	6KV	
Torque(N-m)	0.34	
Screw	M3	
Wire strip length	6~7mm	



Pole	Cat.No.
02	166-02P3
:	:
:	:
12	166-12P3



166..P5



Pitch: 10.00mm

Approval		
Technical Data	UL	IEC
Rated voltage	300V / 600V	450V
Rated current	12A	24A
Conductor cross-section, solid (AWG/mm ²)	18-12	0.5-4
Conductor cross-section, flexible (AWG/mm ²)	18-12	0.5-4
Rated impulse voltage	8KV	
Torque(N-m)	0.34	
Screw	M3	
Wire strip length	6~7mm	

Pole	Cat.No.
02	166-02P5
:	:
:	:
12	166-12P5