



**144R-..P1**




Pitch:3.81mm

Approval		
Technical Data	UL	IEC
Rated voltage	300V	250V
Rated current	10A	17.5A
Conductor cross-section, solid (AWG/mm <sup>2</sup> )	20-14	0.5-1.5
Conductor cross-section, flexible (AWG/mm <sup>2</sup> )	20-14	0.5-1.5
Rated impulse voltage	4KV	
Torque(N-m)		
Wire strip length	6-7mm	
End cover	144E	
Pole	Cat.No.	
02	144R-02P1	
:	:	
:	:	
24	144R-24P1	




**144R-..P2**




Pitch:3.96mm

Approval		
Technical Data	UL	IEC
Rated voltage	300V	250V
Rated current	10A	17.5A
Conductor cross-section, solid (AWG/mm <sup>2</sup> )	20-14	0.5-1.5
Conductor cross-section, flexible (AWG/mm <sup>2</sup> )	20-14	0.5-1.5
Rated impulse voltage	4KV	
Torque(N-m)		
Wire strip length	6-7mm	
End cover	144E	
Pole	Cat.No.	
02	144R-02P2	
:	:	
:	:	
24	144R-24P2	




**144R-..P**




Pitch:5.00mm

Approval		
Technical Data	UL	IEC
Rated voltage	300V	450V
Rated current	10A	24A
Conductor cross-section, solid (AWG/mm <sup>2</sup> )	20-14	0.5-2.5
Conductor cross-section, flexible (AWG/mm <sup>2</sup> )	20-14	0.5-2.5
Rated impulse voltage	4KV	
Torque(N-m)		
Wire strip length	6-7mm	
End cover	144E	
Pole	Cat.No.	
02	144R-02P	
:	:	
:	:	
24	144R-24P	



**144R-..P3**




Pitch:7.50mm

Approval		
Technical Data	UL	IEC
Rated voltage	300V	750V
Rated current	10A	24A
Conductor cross-section, solid (AWG/mm <sup>2</sup> )	20-14	0.5-2.5
Conductor cross-section, flexible (AWG/mm <sup>2</sup> )	20-14	0.5-2.5
Rated impulse voltage	6KV	
Torque(N-m)		
Wire strip length	6-7mm	
End cover	144E	
Pole	Cat.No.	
02	144R-02P3	
:	:	
:	:	
24	144R-24P3	



**144RA-..P1**




Pitch:3.81mm

Approval		
Technical Data	UL	IEC
Rated voltage	300V	250V
Rated current	10A	17.5A
Conductor cross-section, solid (AWG/mm <sup>2</sup> )	22-14	0.5-1.5
Conductor cross-section, flexible (AWG/mm <sup>2</sup> )	22-14	0.5-1.5
Rated impulse voltage	4KV	
Torque(N-m)		
Wire strip length	6-7mm	
End cover	144E	
Pole	Cat.No.	
02	144RA-02P1	
:	:	
:	:	
24	144RA-24P1	



**144RA-..P2**




Pitch:3.96mm

Approval		
Technical Data	UL	IEC
Rated voltage	300V	250V
Rated current	10A	17.5A
Conductor cross-section, solid (AWG/mm <sup>2</sup> )	22-14	0.5-1.5
Conductor cross-section, flexible (AWG/mm <sup>2</sup> )	22-14	0.5-1.5
Rated impulse voltage	4KV	
Torque(N-m)		
Wire strip length	6-7mm	
End cover	144E	
Pole	Cat.No.	
02	144RA-02P2	
:	:	
:	:	
24	144RA-24P2	



**144RA-..P**




Pitch:5.00mm

Approval		
Technical Data	UL	IEC
Rated voltage	300V	450V
Rated current	10A	24A
Conductor cross-section, solid (AWG/mm <sup>2</sup> )	20-14	0.5-2.5
Conductor cross-section, flexible (AWG/mm <sup>2</sup> )	20-14	0.5-2.5
Rated impulse voltage	4KV	
Torque(N-m)		
Wire strip length	6-7mm	
End cover	144E	
Pole	Cat.No.	
02	144RA-02P	
:	:	
:	:	
24	144RA-24P	



**144RA-..P3**



Pitch:7.50mm

Approval		
Technical Data	UL	IEC
Rated voltage	300V	750V
Rated current	10A	24A
Conductor cross-section, solid (AWG/mm <sup>2</sup> )	20-14	0.5-2.5
Conductor cross-section, flexible (AWG/mm <sup>2</sup> )	20-14	0.5-2.5
Rated impulse voltage	6KV	
Torque(N-m)		
Wire strip length	6-7mm	
End cover	144E	
Pole	Cat.No.	
02	144RA-02P3	
:	:	
:	:	
24	144RA-24P3	