



Wire Protector

NO POSN	DIM A
2	14.2 ± 0.3
3	22.4 ± 0.3
4	30.6 ± 0.5
5	38.8 ± 0.5
6	47.0 ± 0.5
7	55.2 ± 0.7
8	63.4 ± 0.7
9	71.6 ± 0.7
10	79.8 ± 0.7
11	88.0 ± 1.0
12	96.2 ± 1.0

ALL DIMENSION IN MM UNLESS OTHERWISE STATED : 0.= ±0.2mm 00.= ±0.4mm

Housing Material : Polyamide 66 (PA66), Nature flame-retardant to UL 94V-2

Voltage : 300V(UL), 450V(VDE)

Current : 20A(UL), 17.5A(VDE)

Working Temperature : T110(IEC), 105° C(UL)

Terminal Body : Brass, nickel-plated

Wire Protector : Stainless spring steel

Screws : M2.6x5, Steel zinc-plated

Wire Range : 0.75 ~ 1.5mm² #22 ~ #12 Sol./Str.

 金筆企業股份有限公司
HEAVY POWER CO., LTD.

TITLE :
TERMINAL BLOCK
Model No. PA8
Part No. PA8HDS

Drawn By

yao

2014. 12. 26

Rev.

A1

International Approvals

UL, CSA, CE, VDE, FIMKO, SEMKO, NEMKO, DEMKO, KEMA, OVE, CEBEC, SEV, CQC, IMQ