



NO POSN	DIM A
2	14.3±0.3
3	22.5±0.3
4	30.7±0.5
5	38.9±0.5
6	47.1±0.5
7	55.3±0.7
8	63.5±0.7
9	71.7±0.7
10	79.9±0.7
11	88.1±1.0
12	96.2±1.0

ALL DIMENSION IN MM UNLESS OTHERWISE STATED : 0.= ±0.2mm 00.= ±0.4mm

Housing Material : Polyamide (PA66), Nature flame-retardant to UL 94V-2

Voltage : 300V(UL), 450V(VDE)

Current : 20A(UL), 17.5A(VDE)

Working Temperature : T110(IEC), 85° C(UL)

Terminal Body : Steel provided with a brass strip, zinc-plated

Wire Protector : Stainless spring steel

Screws : M2.6x5, Steel zinc-plated

Wire Range : 0.75 ~ 1.5mm<sup>2</sup> #22 ~ #12 Sol./Str.

International Approvals

UL, CE, VDE, FIMKO, CQC

 金筆企業股份有限公司  
HEAVY POWER CO., LTD.

TITLE :  
TERMINAL BLOCK  
Model No. PA7DS  
Part No. PA7DS

Drawn By

*yao*

2014. 12. 26

Rev.

A1