



NO POSN	DIM A
2	22.8 ± 0.3
3	36.3 ± 0.5
4	49.8 ± 0.5
5	63.3 ± 0.7
6	76.8 ± 0.7
7	90.3 ± 0.7
8	103.8 ± 1.0
9	117.3 ± 1.0
10	130.8 ± 1.5
11	144.3 ± 1.5
12	158.0 ± 1.5

ALL DIMENSION IN MM UNLESS OTHERWISE STATED : 0.= ±0.2mm 00.= ±0.4mm

Housing Material : Polyamide (PA66), Nature flame-retardant to UL 94V-2

Voltage : 300V(UL), 500V(VDE)

Current : 50A(UL), 57A(VDE)

Working Temperature : T110(IEC), 105° C(UL)

Terminal Body : Brass, nickel-plated

Wire Protector : Stainless spring steel

Screws : M4.0x9, Steel zinc-plated

Wire Range : 4 ~ 10mm², #20 ~ #8 Sol/Str

 金筆企業股份有限公司
HEAVY POWER CO., LTD.

TITLE :
TERMINAL BLOCK
Model No. PA14HDS
Part No. PA14HDS

Drawn By

yao

Rev.

International Approvals
UL, VDE, FIMKO, SEMKO, CQC, CE

2014.12.29

A1