



NO POSN	DIM A
2	16.6 ± 0.3
3	26.6 ± 0.5
4	36.6 ± 0.5
5	46.6 ± 0.7
6	56.6 ± 0.7
7	66.6 ± 0.7
8	76.6 ± 1.0
9	86.6 ± 1.0
10	96.6 ± 1.0
11	106.6 ± 1.5
12	116.8 ± 1.5

ALL DIMENSION IN MM UNLESS OTHERWISE STATED : 0.= ±0.2mm 00.= ±0.4mm

Housing Material : Polypropylene (PP), white flame-retardant to UL 94V-2

Voltage : 300V(UL), 450V(VDE)

Current : 25A(UL), 41A(VDE)

Working Temperature : T85(IEC), 65°C(UL)

Terminal Body : Steel, zinc-plated

Screws : M3.0x6, Steel zinc-plated

Wire Range : 1 ~ 6mm², #22 ~ #10 Sol. / #14 ~ #10 Str.

 金筆企業股份有限公司
HEAVY POWER CO., LTD.

TITLE :
TERMINAL BLOCK
Model No. PA30P
Part No. PA30P

Drawn By

Rev.

International Approvals

UL, CE, VDE, FIMKO, CQC

Lily
2017. 11. 30

A3