



NO POSN	DIM A
2	14.2±0.3
3	22.4±0.3
4	30.6±0.5
5	38.8±0.5
6	47.0±0.5
7	55.2±0.7
8	63.4±0.7
9	71.6±0.7
10	79.8±0.7
11	88.0±1.0
12	96.2±1.0

ALL DIMENSION IN MM UNLESS OTHERWISE STATED : 0.= ±0.2mm 00.= ±0.4mm

Housing Material : Polyamide (PA66), Nature flame-retardant to UL 94V-2

Voltage : 300V (UL), 450V (VDE)

Current : 20A (UL), 17.5A (VDE)

Working Temperature : T110 (IEC), 105° C (UL)

Insert : Brass, nickel-plated

Screws : M2.6x5, Steel zinc-plated

Wire Range : 0.75 ~ 1.5mm² #22 ~ #12 Sol./Str.



金筆企業股份有限公司
HEAVY POWER CO., LTD.

TITLE :
TERMINAL BLOCK
Model No. PA8
Part No. PA8H

Drawn By

Max
2015.08.10

Rev.

A2

International Approvals

UL, CSA, CE, VDE, FIMKO, SEMKO, NEMKO, DEMKO, KEMA, OVE, CEBEC, SEV, CQC, IMQ